



PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Surface treatment	Oil This floor should be oiled immediately after installation.	Design	3-strip	Moisture	EN13183	7%±2%
		Grading	Dynamic	content		
		Range	Kährs Original	Minimun Mean Density kg/m <sup>3</sup> >500 kg/m <sup>3</sup>		
Dimensions	2419 x 196 x 15 mm	Collection	Götaland Collection	Reaction To Fire	EN13501-1	Dfl-s1
Veight per Package (kg)	22.4 kg	Resandable	2-3 times	Formaldehyde Emission	EN717-1	E1
Area per Package (m²)	2.8 m <sup>2</sup>	Natural/Stained	Stained			
Area per pallet (m²)	113.6 m <sup>2</sup>	Brinell Value	3,7	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5S	Breaking Strength	EN1533	NPD
		Floor heating	Yes	N/mm <sup>2</sup>		
		Warranty	30 years	Thermal	EN12664	0,14 W/mK
		Wear-layer material	Hardwood	Conductivity		
DETAIL DESCRIPTION		Wear Layer Thickness (mm)	3.5 mm	Thermal Resista	ance R-Value	.11 (m2K/W)
Contains knots and all natural colour variations.				Biological	EN350-2	Class 1
		Core material	Pine/Spruce/Alder	Durability		
COLOUR CHANGE Thic		Thickness (mm)	15 mm	CARB2		Compliant
The colour matures over time		Installation method	Floating, Glue-down	Slipperiness	CEN/TS15676	NPD
		Surface Colour	Grey			

AB GUSTAF KÄHR | www.kahrs.com | © Kährs 2022

## Other products in this collection





Oak Backa



Oak Vinga



Oak Attebo



Oak Kilesand

Oak Boda

## CERTIFICATES



## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.