

Technical Data




Covering type according to ISO 10582	Heterogeneous Planks / Tiles, type 1
Number of colours	77 planks / 27 tiles
Packaging per box/pallet	3.34 m ² /240.48 m ² 600x600 mm: 3.24 m ² /233,28 m ²
Performance classification EN ISO 10582 / ISO 10874	23/ 31
Total thickness ISO 24346	2.0 mm
Wearlayer thickness ISO 24340	0.3 mm
Surface treatment	yes/PU
Bevelled edges	yes (depending on design)
Total weight ISO 23997	3.51 kg/m ²
Residual indentation ISO 24343-1	≤ 0.1 mm*
Dimensional stability ISO 23999	≤ 0.15 %*
Castor chair suitability ISO 4918	yes – using EN 12529, type W
Underfloor heating EN 1264-2	suitable up to 28°C
Behaviour to fire EN 13501-1	Bfl-s1
Resistance to thermal conductivity ISO 8302/ EN 12667	0.02 m ² K/W
Electrical propensity when walked upon EN 1815	< 2 kV
Impact sound improvement ISO 10140-3	2 dB
Colour fastness to artificial light ISO 105-B02/02	≥ 7
Electrostatic characteristics EN 1081	> 10 ¹²
Chemical resistance ISO 26987	conforms**
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)
Adhesive recommendation	see installation instruction
Maintenance/Cleaning recommendation	Dr. Schutz

* Averaged value

(Date: 01/01/2019)

** Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.



Impressum / Imprint